## **Specifications**

### T100



Hardware	
Size	279mm x 200mm x 18.5mm (11" x 7.9" x 0.7")
Weight	1.65kg (3.6lb)
Memory	16 GB SDRAM
Storage	512 GB SSD
Processor	Intel® Core™ i5
Operating system	Microsoft Windows 10 Professional
Power	
Battery	92Wh internal non-removable
Battery Life	10 Hours @ 20C with GPS on [1]
Charging Time	1:15 to 50%, 3 hours to 100% [1]
AC/DC Power	AC 100~240V, 50~60Hz
	DC 5V, 9V, 15V, 20V, 65W
Environmental	
Temperature – Operating	–20°C to +55 °C (–4°F to 131°F) [2]
Temperature – Storage	-40 °C to +70 °C (-22 °F to +158 °F)
Humidity	0% - 95% non-condensing
Water and Dust	IP65, IEC 60629 Edition 1
Drops	MIL STD 810H Method 516.8 Procedure IV- Transit Drop
Vibration/ Shock	MIL STD 810H Method 514.8 Procedure I - Random Vibration
Altitude	MIL STD 810H Method 514.8 Procedure II - Loose Cargo Transport Operating 5°C and 30,000 feet
	Non-Operating -30°C and 40,000 feet
Interface	
Display – General	LED backlight scratch-resistant, auto-rotate
Display - General Display- Size	10" Capacitive multi-touch
Display – Resolution	1920 x 1200
User Interface	Power button, directional pad, programmable function keys, power/battery status LED, on screen
User Internate	rower button, directional pad, programmable function keys, power/battery status LED, on screen

Integrated speaker and microphone

8MP with flash, rear facing

USB 3.0 Type C x2

Yes, 2 slots

**Communications** Wi-Fi

Audio

I/O

Camera

Empower

Wi-Fi 802.11ac

# **S**pecifications

#### **T100**



Bluetooth	Bluetooth v5.1
Cellular	4G LTE worldwide coverage, certified on Verizon and AT&T
GNSS	GPS L1 C/A, QZSS, Glonass, Galileo, Beidou, SBAS
Other	
Sensors	E-compass, accelerometer, gyroscope, ambient light sensor, proximity sensor
	[1] Battery operation and recharge times will vary based on many factors, including screen brightness, applications, features, power management, battery conditioning and other settings.
	[2] Tested under MIL-STD-810H method 501.6, Procedure II, and method 502.6, Procedure II. Battery capacity is reduced at lower temperatures or extremely high temperatures. Batteries should neither be charged at temperatures below 0C or temperatures above 45C to avoid impacting battery longevity and performance.
Specifications subject to change without notice.	© 2021, Trimble. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble registered in the United States and in other countries. Trimble Tablet T100 is a trademark of Trimble. Microsoft, Windows, Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. All other brand names and trademarks are property of their owners. Color display images shown may vary slightly from actual display. (04/21)

#### Trimble Civil Engineering and Construction Division

10368 Westmoor Drive Westminster, Colorado 80021 USA 800-361-1249 (Toll Free) +1-937-245-5154 Phone +1-937-233-9441 Fax www.trimble.com