

Specifications

Trimble SPS785 GNSS Smart Antenna



Receiver Name	SPS785 GNSS Smart Antenna
GNSS Characteristics	
-240 GNSS Channels	GPS L1C/A, L2P(Y), L2C GLONASS L1C/A, L2C/A, L3 BeiDou B1 (phase 2), B2 Galileo E1, E5b QZSS L1C/A, L2C, L1 SAIF SBAS L1C/A L-band
-Patented Z-Blade technology for optimal GNSS performance	-Full utilization of signals from all 6 GNSS systems -Enhanced GNSS-centric algorithm: fully independent GNSS signal tracking and optimal data processing, including GPS-only, GLONASS only or BeiDou only solution (autonomous to full RTK)
-Patented SBAS ranging for using SBAS code & carrier observations and orbits in RTK processing	-Fast search engine for quick acquisition and re-acquisition of GNSS signals
-Patented Strobe Correlator for reduced GNSS multi-path	
-Up to 10Hz real-time raw data (code & carrier and position output)	
-Supported data formats	ATOM,CMR, CMR+ RTCM 2.1, 2.3, 3.0, 3.1, and 3.2 (including MSM) CMRx (rover only)
-NMEA 0183 message output	
Real-Time Accuracy (RMS) [1,2] SBAS (WAAS/EGNOS/MSAS/GAGAN)	Horizontal: < 50cm Vertical: <85cm
Real-Time DGPS Position	Horizontal: 25cm + 1 ppm Vertical: 50cm + 1 ppm
Real-Time Kinematic Position (RTK)	Horizontal: 8mm + 1 ppm Vertical: 15mm + 1 ppm
Real-Time Performance	RTK initialization range: over 40 km Instant RTK initialization -Typically 2 sec for baselines < 20km -Up to 99.9% reliability
Post Processing Accuracy (RMS) [1,2] Static & Fast Static	Horizontal: 3mm + 0.5 ppm Vertical: 5mm + 0.5 ppm
High-Precision Static[3]	Horizontal: 3mm + 0.1 ppm Vertical: 3.5mm + 0.4 ppm

Specifications

Trimble SPS785 GNSS Smart Antenna



Post-Processed Kinematic (PPK)	Horizontal: 8mm + 1 ppm Vertical: 15mm + 1 ppm
Data Logging Characteristics	
Recording Interval	0.1 - 999 seconds
Physical Characteristics	
Size	21 x 21 x 7 cm (8.3 x 8.3 x 2.3 in)
Weight	930 g (2.08 lb)
User Interface	Five LEDs for power, tracking, Bluetooth, recording, and radio
I/O Interface	-RS232 serial link -USB 2.0/UART and USB OTG -Bluetooth 2.1 + EDR, Long range: class 1 (19dbm)
Memory	-256 MB internal memory NAND flash
Operation	-Over a month of 15 sec. raw GNSS data from 14 satellites -RTK rover and base -RTK network rover: VRS, FKP, MAC -NTRIP, Direct IP -Post processing
Environmental characteristics	Operating temperature: -40°C to +65°C (-40°F to +149°F)[4] Storage temperature: -40°C to +85°C (-40°F to +185°F)[5] Humidity: 100% condensing IP67 waterproof, sealed against sand and dust Drop: 2m pole drop on concrete Shock: MIL STD (fig 516.5-10) (01/2000) Vibration: MIL STD-810F (fig 514.5C-17) (01/2000)
Power characteristics	External DC power: 9-28 V Li-ion battery, 7.4 V, 2600 mAh Battery Life 10 hrs (GNSS on, 400MHz Rx off) 8 hrs (GNSS on, 400MHz Rx on) 5 hrs (GNSS on, 900MHz Rx on)
System	
Standard system components	-SPS785 receiver -Li-ion battery -Dual battery charger, power supply and power cord kit -Tape measure (3.6 m / 12 ft) -7cm pole extension -USB to mini-USB cable SPS785 Office power kit -1 year warranty
Optional system components	SPS785 UHF Kit (410-470 MHz 2W TRx) SPS785 900MHz Kit (Receive Only) [7] SPS785 Field power kit Data Collectors -TSC7



-Site Tablet 10
-T10
Field Software
Trimble Siteworks

1. Accuracy and TTFF specifications may be affected by atmospheric conditions, signal multipath, satellite geometry and corrections availability and quality.
2. Performance values assume minimum of five satellites, following the procedures recommended in the product manual. High multipath areas, high PDOP values and periods of severe atmospheric conditions may degrade performance.
3. Long baselines, long occupations, precise ephemeris used.
4. At very high temperatures UHF module should not be used in the transmitter mode. With UHF transmitter on radiating 2W of RF power, the operating temperature is limited to +55°C (+131°F).
5. Without batteries. Batteries can be stored up to +70°C (+158°F)
6. Receiver initialization time varies based on GNSS constellation health, level of multipath, and proximity to obstructions such as large trees and buildings.
7. 900MHz radio is only available in the US and Canada.

© 2019, Trimble Inc. All rights reserved. Trimble, the Globe & Triangle logo, are trademarks of Trimble Inc., registered in the United States and in other countries. CMR, CMR+, CMRx, xFill, OmniSTAR, CenterPoint RTX, and VRS are trademarks of Trimble Inc. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Inc. is under license. All other trademarks are the property of their respective owners.
06/2019

Trimble Civil Engineering and Construction Division

10368 Westmoor Drive
Westminster, Colorado 80021
USA
800-361-1249 (Toll Free)
+1-937-245-5154 Phone
+1-937-233-9441 Fax
www.trimble.com

Trimble Authorized Distribution Partner

Specifications

Trimble SPS785 GNSS Smart Antenna

